

		Size		Head Type				Base Material				Corrosion Resistance			Features		Approvals	
		Minimum Size	Maximum Size	Stud (Externally Threaded)	Flush or Internally Threaded	Hex Bolt	Rebar	Round/Mushroom	Concrete	Lightweight Concrete	Grout-filled Block	Hollow Block/Brick	Hot-dip Galvanized Steel	304 Stainless Steel	316 Stainless Steel	Seismic ⁺	Cracked Concrete (per ICC-ES)	1: FM 2: UL 3a: ICC Concrete Masonry 3b: ICC Grouted Masonry 3c: ICC Hollow Masonry 4: COLA 5: Miami-Dade 6: NSF 61
Chemical	HIT HY 150 MAX-SD ** Hybrid Adhesive		3/8"	1"	■				■	□			■	■	■	■	■	3a, 4, 6
	HIT HY 150 MAX ** Hybrid Adhesive		3/8"	1-1/4"	■	■			■	□	■	□	■	■	■	■	■	3a, 3b, 4, 5, 6
	HIT RE 500-SD ** Epoxy Adhesive		3/8"	1-1/4"	■	■			■	□			■	■	■	■	■	3a, 4, 6
	HIT RE 500 Epoxy Adhesive		3/8"	>1-1/4"	■	■			■	□			■	■	■	■	■	6
	HIT HY 20 ** Hybrid Adhesive		3/8"	3/4"	■	■			□	□		■	■	■	■	■	■	3c, 4
	HVU Adhesive Capsule		3/8"	1-1/4"	■	■			■	□	□		■	■	■	■	■	6
	HIT-ICE Cold Weather Adhesive		3/8"	1-1/4"	■	■			■	■	■	□	■	■	■	■	■	
	HY 10 Hybrid Adhesive		3/8"	1/2"	■	■			■	□	■	■	■	■	■	■	■	
	HFX Hybrid Adhesive		3/8"	1/2"	■	■			■	□	■	■	■	■	■	■	■	
Mechanical	HDA *** Undercut Anchor		M10	M20	■				■	□			■		■	■	■	3a, 4
	HSL-3 ** Expansion Anchor		M8	M24	■	■			■	□					■	■	■	3a, 4
	HSL Expansion Anchor		M10	M20	■	■			■	□					■		■	
	KB-TZ *** Expansion Anchor		3/8"	3/4"	■				■	■					■	■	■	1, 2, 3a
	KWIK Bolt 3 ** Expansion Anchor		1/4"	1"	■	■			■	■	■		■	■	■	■	■	1, 2, 3a, 3b, 4, 5
	KWIK HUS-EZ ** Screw Anchor		1/4"	3/4"			■		■	■	□*				■	■	■	3a, 3b*, 4*
	KWIK HUS Screw Anchor		3/8"	3/4"			■		■	■	□*							
	HCA Reusable Coil Anchor		1/4"	3/4"			■		■	□								
	HLC Sleeve Anchor		1/4"	3/4"	■	■		■	■	□	■		■					2
	HDI / HDI-L Flush Anchor		1/4"	3/4"	■				■	■			■	303 SS				1, 2
	HDI-P Flush Anchor		3/8"	3/8"	■				■	□		□						
	HCI Cast-in Anchor		1/4"	3/4"	■				■	■								1, 2
	KWIK-CON II Screw Anchor		3/16"	1/4"	■	■			■	□	□	■		■	410 SS			5

■ Suitable □ Application Specific Suitable * Approval pending ** 2009 IBC Compliant Anchor *** 2006 IBC Compliant Anchor +Per ICC-ESR Seismic Design Categories A - F

Additional sizes may be available through special order. Contact Hilti or refer to the Hilti Product Technical Guide for additional information.

Hilti. Outperform. Outlast.

Hilti, Inc. (U.S.) 1-800-879-8000 www.us.hilti.com • en español 1-800-879-5000
Hilti (Canada) Corp. 1-800-363-4458 www.hilti.ca

www.facebook.com/HiltiNorthAmerica

www.youtube.com/HiltiNorthAmerica